

C-POSTS SCREWED BACK-TO-BACK
(or TO 65mm POSTS) USING 8x
10gx16mm TEK SCREWS SPACED
300mm APART

PROFILED PLASTIC CAP
(NOT SHOWN) FITTED
OVER C-POSTS

2250 POST CENTRES

137.5

1800

65x65 FLANGED POST

RAILS SCREWED INTO
C-POSTS USING 2x
10gx16mm TEK SCREWS

Detail A
1:2.5

CONCRETE 17.5mpa MIN

SLOPE TOP OF CONCRETE
TO ALLOW WATER TO
DRAIN AWAY FROM POST

65x65
INGROUND POST

300 DIA
or 250x250 SQUARE

100

'GOOD GROUND'
100kpa ALLOWABLE
BEARING AS DEFINED
BY NZS:3604

275

137.5

28

B
1:6

Fentec

Terranota Ltd. P.O. Box 1703 Invercargill 1703

Telephone: 0800 002 725

Email: sales@fentec.co.nz

Website: www.fentec.co.nz

Model

EasyWall Vertical
Panel 1800mm
FEWV100

Rail profile

50mm roll-formed steel EasyWall rail

Post caps

External plastic profiled caps

C-post profile

65x50mm roll-formed steel EasyWall c-post

Flanged post

65x65x1900mm pre-galvanised powdercoated
steel (125mm square flange) M12 fixings

Panel length

2250x1800mm

Inground post

65x65x2500mm pre-galvanised powdercoated steel

Size
A4

Date issued
2023-03-31

Rev

**DO NOT SCALE
DRAWING**

Sheet
1 of 1

Weight

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS